

2027 OUTLANDER ELECTRIC T



White

PACKAGE HIGHLIGHTS

- Liquid-cooled system : Battery, inverter, motor and on-board charger (charging cable not included, sold as accessory)
- Charging from 20% to 80% in as low as 50 min
- Up to 50 miles (80 km) of range
- High and Low gear allowing full work capacity
- Engine modes and speed limiter
- Dedicated tires for optimal noise and vibrations level
- 3-level regen braking
- On-the-fly reverse capabilities
- 5 in. colored display
- Front and rear bumpers
- LED headlights and tail lights, specific LED POD light
- Tow ball, mirrors, flashers

ENGINE

Electric

Type	47 hp (35kW) / 72 Nm, ROTAX® E-POWER, Liquid-cooled
Power	Peak: 47 hp (35 kW) Continuous: 27 hp (20 kW)
Torque motor	Peak: 72 Nm Continuous: 28 Nm
Top Speed/Sustained	High gear: 37 mph (60 km/h) Low gear: 28 mph (45 km/h)

BATTERY

Battery type	Integrated, Lithium-ion
Battery operating temperature range	From -20°C to 40°C (-4 Fahrenheit to 104 Fahrenheit)
Battery capacity	8.9 kWh
Cooling system	Liquid-cooled : Battery, inverter and on-board charger (charging cable not included, sold as accessory) Integrated AC heater for charging at low temperature
Estimated range (when fully charged)	Tested in accordance with WMTC*: 50 miles (80 km) Average utility range*: 31 miles (50 km)
Fonction	Regen braking with 3 levels adjustments
Charger	On-board charger 6.6 kW Level 2 (compatible with level 1 charging) - charging cable not included, sold as accessory
Connector type	Type 2 IEC 62196 with integrated LED light
Charging time Level 2 (240 V)	50 min (20 - 80 %) 1 hour 30 min (0 - 100%)
Charging time Level 1 (120 V)	3 hours 10 min (20 - 80%) 5 hours 15 min (0 - 100%)

DRIVE TRAIN

Transmission	L / N / H / P - Reverse activated via start button
Drive Train	Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential
Driving assistance	Work / Standard / Sport modes Speed limiter
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm - 9.75 in. (24.8 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-arm - 10.25 in. (26 cm) travel
Rear Shocks	Twin tube

TIRES / WHEELS

Front & Rear Tires	XPS Recon Force 26 x 8/10 x 14 in.
Wheels	14 in. cast aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES

Estimated Dry Weight	885 lb (402 kg)
L x W x H	89.9 x 48.1 x 49.6 in. (228.3 x 122.2 x 126 cm)
Wheelbase	53 in. (134.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38 in. (96.7 cm)
Rack Capacity	Front: 54.4 kg / Rear: 109 kg
Storage Capacity	34 L
Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes

FEATURES

Gauge	5 in. colored display
DC - DC converter	Continuous 500W (at all speed including at idle)
Instrumentation	Phone charger with 1xUSB-A and 1xUSB-C outputs
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and tail lights LED signature LED POD light
Winch	N/A
Seat	Standard
Handlebar	Standard
Protection	Front and rear bumpers Full skid plate
Hitch Type	2 in. hitch receiver with towball

WARRANTY & EXTENDED SERVICE

Factory warranty	Battery: 5 years (12,427 miles / 20,000 km limit) Vehicle: 2-year BRP Limited warranty
------------------	---

REQUEST A QUOTE



©2026 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

